



# T-REX Hybrid Inverter

T-REX-50KHP3G01



## Product Features



3.5-inch LCD touch screen



Smart Cloud Monitoring System



2 independent battery inputs



Programmable generator port



Support multi Working mode



The maximum support is 12 parallel machines.



Ip65 protection grade

# Specification

<b>Model</b>	T-REX-50KHP3G01
<b>Battery Input Data</b>	
Battery Type	LFP (LiFePO4)
Battery Voltage Range	160~800Vd.c.
Max. Charging Current	50+50(A)
Max. Discharging Current	50+50(A)
Number of battery input	2
<b>PV String Input Data</b>	
Max. DC Input Power	65 kW
Max. DC Input Voltage	1000Vd.c.
Min. DC Input Voltage	150Vd.c.
Start-up Voltage	250Vd.c.
Rated DC Input Voltage	600Vd.c.
MPPT Range	200~850Vd.c.
Full Load DC Voltage Range	450~850Vd.c.
PV Input Current	36+36+36+36(A)
Max. PV Isc	55+55+55+55(A)
No.of MPP Trackers	4
No.of Strings per MPP Tracker	2
<b>AC Output Data</b>	
Rated AC Output Power	50 kW
Max. AC Output Power	55 kW
AC Output Rated Current	72.5 A
Max. AC Current	79.7 A
Rated AC Voltage	220/380,230/400 Vac (-20%~ +15%)
AC Wiring Mode	3W+N+PE/3W+PE
Rated AC Frequency	50 /60 Hz (45~55Hz/55~65Hz)
THDI	<3% (At Rated Power)
Power Factor	0.8( leading) to 0.8( lagging)
<b>Efficiency</b>	
Max. efficiency	97.6%
Euro efficiency	97.0%
MPPT efficiency	99.9%
<b>Protection</b>	
PV Input Lightning Protection, PV String Input Reverse Polarity Protection, Battery Input Lightning Protection, Battery Input Reverse Polarity Protection, Insulation Resistor Detection, Residual Current Monitoring Unit, Output Over Current Protection, Output Shorted Protection, Output Over Voltage Protection, Anti-islanding Protection, AC Output Lightning Protection.	Integrated
<b>Certification and Standards</b>	
Grid Regulation	NRS 097-2-1,VDE4105,EN50549-1,AS 4777.2,GB/T 34120,GB/T 34133,GB/T 34129
Safety EMC / Standard	IEC/EN 61000-6-1/2/3/4,IEC/EN 62109-1,IEC/EN 62109-2
<b>General Data</b>	
Protection Degree	IP65
Operating Temperature Range	-25 to 60 °C (> 50 °C derating)
Humidity	0 ~ 95 % (No condensation)
Cooling	Smart cooling
Altitude	3000 m (> 2000 m derating)
Communication with BMS	RS485,CAN
Monitor module	WiFi/GPRS
Installation Style	Wall-mounted
Warranty[1]	10 years
Net Weight(KG)	85.6KG
Gross Weight(KG)	98.4KG
Product Dimension(MM)	940*340*582MM
Package Dimension(MM)	463*770*1110MM

[1]Conditions apply, refer to FelicityESS Warranty Letter.

\*According to local grid-connected standards